

Three-Way Horn-Loaded Loudspeaker



Cornwall III

Initially introduced in 1959, the Cornwall speaker was designed to serve as a larger, full-range alternative to the Heresy when used as a center channel speaker between two widely spaced Klipschorns. When it was discontinued in 1990, there was an outcry from consumers resulting in a letter-writing campaign and even a petition to bring back this storied loudspeaker.

This famed speaker, now dubbed the Cornwall III, is back and better than ever. A three-way design using horn-loaded compression drivers for the midrange and treble and a direct-radiating 15-inch woofer for the low frequencies, the Cornwall delivers the full-range bass response of the Klipschorn® with sensitivity and output approaching the fully horn-loaded models.

S P E C I F I C A T I O N S

FREQUENCY RESPONSE	34Hz-20kHz \pm 3dB
SENSITIVITY	102dB @ 1 Watt/1 meter
POWER HANDLING	100 Watts max continuous (400W peak)
MAXIMUM SPL	119dB
NOMINAL IMPEDANCE	8 ohms
ENCLOSURE TYPE	Bass reflex via front-mounted slot ports
CROSSOVER FREQUENCY	HF: 5000Hz MF: 800Hz
TWEETER	K-107-TI 1" (2.54cm) Titanium diaphragm compression driver
HIGH FREQUENCY HORN	Tractrix®
MIDRANGE	K-53-TI 1.75" (4.45cm) Titanium diaphragm compression driver
MID-FREQUENCY HORN	Exponential
WOOFER	K-33-K 15" (38.1cm) Fiber-composite cone
DIMENSIONS	35.75" (90.81cm) H x 25.313" (64.29cm) W x 15.5" (39.37cm) D
WEIGHT	98 lbs. (44.5kg)
ENCLOSURE MATERIAL	MDF
FINISHES	Walnut Lacquer, Cherry Lacquer, Black Lacquer



www.klipsch.com
1-800-KLIPSCH

All specifications are subject to change without notice. ©2006