

Contour

DYNAUDIO
AUTHENTIC FIDELITY





The Contour S 5.4

A burning passion drives the longing for dynamism and power. The art of creating a loudspeaker that transcends time and achieves a level of perfection in sound quality is driven by this same passion. Born from this passion is the performance of the Contour S 5.4.

The powerful neodymium magnets, the precisely formed aluminium voice coils and the stiff MSP cone membranes

demand a solid foundation to deliver maximum dynamics and an ideal impulse response. Thus, the front of the loudspeaker is reinforced by a solid metal baffle, fused to the wooden cabinet by a resonance-absorbing damping panel. This highly rigid construction provides an ideal foundation for the high-performance Dynaudio drivers to perform at their fullest potential. Additionally, the components need to operate in a stable thermal environment. The crossover of the

Technical Specifications

	Contour S 5.4	Contour S 3.4	Contour S 1.4	Contour S CX	Contour S C	Contour S R
Sensitivity	(2.83 V/1 m): 89 dB	(2.83 V/1 m): 88 dB	(2,83 V/1 m): 85 dB	(2.83 V/1 m): 87 dB	(2.83 V/1 m): 86 dB	(2.83 V/1 m): 86 dB
IEC Long Term Power Handling	350 watts (4 ohms)	300 watts (4 ohms)	170 watts (4 ohms)	300 watts (4 ohms)	150 watts (4 ohms)	100 watts (4 ohms)
Impedance, Nominal	4 ohms	4 ohms	4 ohms	4 ohms	4 ohms	4 ohms
Bass Principle	Reflex	Reflex	Reflex	Reflex	Reflex	Sealed Enclosure
Weight	46 kg	40 kg	12 kg	18 kg	10 kg	5 kg
Dimensions (W x H x D)	214 x 1450 x 390 mm 8.4 x 57.1 x 14.4 "	190 x 1220 x 340 mm 7.5 x 48.1 x 13.4 "	188 x 400 x 340 mm 7.4 x 15.8 x 13.4 "	800 x 193 x 318 mm 31.5 x 7.6 x 12.5 "	490 x 230 x 260 mm 19.3 x 9.1 x 10.2 "	165 x 275 x 140 mm 6.5 x 10.8 x 5.5 "
Crossover Slope	6 dB/oct	6 dB/oct	6 dB/oct	6 dB/oct	6 dB/oct	6 dB/oct
Tweeters	Esotar ² 28 mm soft dome	Esotec 28 mm soft dome	Esotec 28 mm soft dome	Esotar ² 28 mm soft dome	Esotec 28 mm soft dome	Esotec 28 mm soft dome
Mid/Woofers	1 x 15 cm MSP-cone, 38 mm pure aluminium wire voice coil	2 x 17 cm MSP-cone, 75 mm pure aluminium wire voice coil	1 x 17 cm MSP-cone, 75 mm pure aluminium wire voice coil	2 x 17 cm MSP-cone, 75 mm pure aluminium wire voice coil	2 x 15 cm MSP-cone, 75 mm pure aluminium wire voice coil	1 x 15 cm MSP-cone, 75 mm pure aluminium wire voice coil
Woofers	2 x 20 cm MSP-cone 75 mm pure aluminium wire voice coil	-	-	-	-	-
Connection	CE-comp. WBT gold binding posts (all models)					
Optional	-	-	Dynaudio Stands	Dynaudio Center Bases	Dynaudio Center Bases	-



Technical specifications are subject to change without notice.

Kapton® is a registered trademark of Dupont.

The Contour models are available in a choice of standard natural veneers. Please consult your authorized Dynaudio dealer for information regarding other finishes which may be available upon request per special order. All shown veneers images can not give a true impression of the finesse and structure of a real wood finish.

All aspects relating to the performance criteria of the Contour line are strictly controlled. Along all stages of the entire production process - from raw material selection to final assembly and quality control - Dynaudio thoroughly inspects each parameter along every step of the way. In turn, all Dynaudio loudspeakers are adorned with a five-year manufacturer's warranty.



DYNAUDIO
AUTHENTIC FIDELITY

www.dynaudio.com

DYNAUDIO A/S
8660 Skanderborg
Denmark

Sales & Marketing

DYNAUDIO International GmbH
Ohepark 2
21224 Rosengarten
Germany
Phone +49 (0)4108 - 4180 - 0



Contour