# IN126STx

Bright short throw projector at a great low price Part #: IN126STx

The InFocus IN126STx short throw projector combines short throw, high brightness, networking, and low cost – making it perfect for the classroom, office or other tight space.

#### **Key Features**

- WXGA (1280 x 800) native resolution
- Short throw lens (0.52 throw ratio)
- Up to 3700 lumens of brightness
- Display over HDMI, VGA, composite or S-video
- Networkable for easy management
- Incredible, sharp images with 14,000:1 contrast ratio
- Compact and light weight for easy portability
- Display 3D content from Blu-ray, PCs and more





## Why Choose the IN126STx Short Throw Projector?

- Big, vivid images from a short distance with no shadow interference
- High brightness that delivers clear images with the lights on
- 14,000:1 contrast ratio delivers incredible sharpness with darker blacks and whiter whites
- Instantly stop projecting from the remote control to lengthen lamp life and save money and energy
- Easily move the projector from room to room or install and manage remotely over the network
- An exceptional 10-watt speaker fills the room with sound

## **Priced Right**

The ultra-low purchase price is just the beginning – the lamp is long-lasting and no filters.

- Great low price to fit your budget
- Use Eco Blanking when the projector isn't used to lower the lamp's power usage and extend its life

- Average lamp life is 5,000 hours in Eco Blanking mode, 3,500 hours when in Eco Mode, and 2,000 hours in normal mode
- No filters to clean or replace

## **Count on Quality**

Even at this incredible low price this projector is made to perform with high-quality image technology you can count on.

- Quality images and true-to-life colors with DLP<sup>®</sup> technology with InFocus BrilliantColor<sup>™</sup> implementation
- Amazing 14000:1 contrast ratio adds sharpness with darker blacks and whiter whites
- Preset modes give you the best image quality on a beige wall, whiteboard, blackboard or other surface
- 3D-ready: project Blu-ray and PC-based 3D content via HDMI to improve learning and retention of complex concepts



#### **Compact Powerhouse**

Compact size makes it easy to move from room-to-room, but powerful enough to install

- HDMI input for fast, high quality display of digital devices
- High brightness that can combat bright lighting situations
- Built in speaker and 3.5mm audio out port provides clear audio
- RS232 port means it can be easily integrated into room control systems





# Specifications\*

Projector	IN126STx
Resolution – Native	WXGA (1280 × 800)
Resolution – Maximum	WUXGA (1920 × 1200)
Display Technology	DLP
Video Standard Compatibility	NTSC, PAL, SECAM, 480i, 480p, 576i, 576p, 720p, 1080i, 1080p
Speakers	Mono 10W x 1
Lamp Brightness	3,700 lumens
Lamp Life	2,000 hours
Lamp Power	260W
Lamp Power – Eco Mode	65W
Replacement Lamp	SP-LAMP-094
Contrast Ratio	14,000:1
Color Wheel	6 segment, 2x speed
Number of Colors	1.07 billion
Aspect Ratio	16:10
Aspect Ratio Compatibility	4:3
Lens Type	Manual focus
Projection Offset	15
Connectors – Inputs	3.5mm stereo audio ×2, RS232, HDMI 1.4, Composite video, S-video, VGA x2, USB Type B (control & firmware), RJ-45 (Ethernet)
Connectors – Outputs	3.5mm audio output, Monitor out (VGA)
Audible Noise	< 34 dBA at 0°F / -17.8°C
Audible Noise – Eco Mode	< 32 dBA at 0°F / -17.8°C
Included Accessories	Power cord, Remote, VGA cable, Documentation
3D Support	1080p @ 120 HZ via HDMI, DLP Link 3D glasses required
Product Warranty	1 year
Lamp Warranty	6 months
Accessories Warranty	90 days
Operating Conditions	32 to 104°F at 0 to 1000 ft / 0 to 40°C at 0 to 304.8 m
Menu Languages	English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Traditional Chinese, Korean, Swedish, Russian, Finnish, Polish, Turkish, Danish, Arabic, Indonesian, Persian, Portuguese, Vietnamese, Czech, Romanian, Hungarian
Security Features	User PIN, Security bar, Security lock slot
Approvals	UL and c-UL, FCC, CE, CCC+CECP, KCC, NOM, PCT/CU/EAC, PSB, SABS, SASO, CB, Nemco/GS, KC
Throw and Zoom	
Throw Ratio – Standard Lens – Maximum	0.52
Shipping	
Product Dimensions	5.1 x 11.8 x 9.1 in / 129.5 x 299.7 x 231.1 mm
Product Weight	5.1 lbs / 2.3 kg
-	

Projector	IN126STx
Shipping Dimensions	7.8 x 14.3 x 12 in / 196.9 x 362 x 304.8 mm
Shipping Weight	7.1 lbs / 3.2 kg

\* Product specifications, terms, and offerings are subject to change at any time without notice.

#### Accessories

Universal Projector Ceiling Mount (PRJ-MNT-UNIV) Motorized Electric Projector Screen: 130 in., 16:10 (SC-MOTW-130) Projector Lamp for the IN120x, IN120STx, and IN2120x Series (SP-LAMP-094) LiteShow 4 Wireless Adapter (INLITESHOW4) Replacement Remote for Meeting Room Projectors (HW-NAVIGATOR-4) Presenter 4 RF Remote with Laser Pointer (HW-PRESENTER-4) Presenter 3 RF Remote with Laser Pointer (HW-PRESENTER-3) Soft Carry Case for Value Projectors (CA-SOFTVAL-2) Projector Ceiling Mount System (Black) (PRJ-MNTKIT-UNIVB) Projector Ceiling Mount System (White) (PRJ-MNTKIT-UNIVW) Manual Pull Down Projector Screen: 94 in., 16:10 (SC-PDW-94) Manual Pull Down Projector Screen: 109 in., 16:10 (SC-PDW-109) Motorized Electric Projector Screen: 94 in., 16:10 (SC-MOTW-94) Motorized Electric Projector Screen: 113 in., 16:10 (SC-MOTW-113) Fixed Frame Projector Screen: 94 in., 16:10 (SC-FFW-94) Fixed Frame Projector Screen: 130 in., 16:10 (SC-FFW-130) VGA Cable (36 ft / 11 m) (SP-VGA-11M) Projector Lock by PC Guardian (SEC-LOCK-01) DLP Link 3D Glasses by XPAND (X103-EDUX3-R1) SMART Mount Adapter (INA-SMRTADPT) 1 Year Extended Warranty for IN1XX Projectors (EPW-PJV1) 2 Year Extended Warranty for IN1XX Projectors (EPW-PJV2)