

CinemaX P2

Ultra short throw smart laser 4K Ultra HD projector



- **Ultra short throw laser projector - 4K UHD resolution, HDR compatible**
- **Amazing colour - extensive DCI-P3 coverage, 3000 ANSI lumens**
- **Integrated soundbar with Dolby Digital 2.0**
- **Smart features - Apps, voice control, IFTTT**

Part of the CinemaX range, this stylish ultra short throw projector delivers an unforgettable 4K UHD digital cinema quality image in the comfort of your own home. Laser technology provides accurate, true to life colour reproduction with extensive DCI-P3 coverage - perfect for recreating the big-screen experience at home.

Packed with the latest technology and features, the CinemaX P2 boasts HDR compatibility, sophisticated PureMotion frame-interpolation processing which eliminates motion blurring or image judder, voice control, streaming apps and a built-in media player.

Specifications

| | |
|------------------------------|--|
| Display/image | |
| Display technology | DLP |
| Resolution | UHD (3840x2160) |
| Brightness | 3,000 lumens |
| Contrast ratio | 2,000,000:1 |
| Native aspect ratio | 16:9 |
| Aspect ratio - compatible | 4:3 |
| Horizontal scan rate | 31 ~ 135KHz |
| Vertical scan rate | 24 ~ 120Hz |
| Uniformity | 90% |
| Screen size | 2,16m ~ 3,05m (85" ~ 120") diagonal |
| Lamp info | |
| Light source type | Laser |
| LASER life | 30,000 hours |
| Optical | |
| Throw ratio | 0,25:1 |
| Projection distance (m) | 0,47m - 0,66m |
| Focal length (mm) | 525 |
| Native offset | 124% |
| Connectivity | |
| Connections | Inputs 2 x HDMI 2.0, 1 x USB-A reader, 1 x RJ45, 1 x HDMI 1.4a 3D support Outputs 1 x S/PDIF, 1 x USB-A power 1.5A, 1 x Audio 3.5mm Control 1 x USB-A service |
| General | |
| Noise level (typical) | 26dB |
| Noise level (max) | 28dB |
| PC compatibility | UHD, WQHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac |
| 2D compatibility | 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz), 2160p(50/60Hz) |
| 3D compatibility | Frame-pack: 1080p24, 720p50 / 60 |
| 3D | Full 3D |
| Security | Kensington Lock, Password protected interface |
| OSD / display languages | 11 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) |
| Operating conditions | 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m |
| Remote control | Yes |
| Speaker count | 2 |
| Watts per speaker | 10W |
| In the box | AC power cord Rechargeable remote control Basic user manual |
| Input lag | 70,00ms |
| Power | |
| Power supply | 100 ~ 240V, 50 ~ 60Hz |
| Power consumption (standby) | 0.5W |
| Power consumption (min) | 220W |
| Power consumption (max) | 345W |
| Weight and dimensions | |
| Net weight | 11kg |
| Dimensions (W x D x H) mm | 576 x 383 x 130 |